

Product Specification

Cladseal EXT

Cladseal EXT is an elastomeric waterproofing strip based on the rubber polymer EPDM with a low water vapour transmission factor. The product is used as a vapour control layer such as façade waterproofing, damp proof course or similar. The product comes in black colour and has a surface texture on both sides for maximum adhesion. Cladseal EXT provide very long expected service life and is an environmental friendly product.

SARLO OT CE

Technical data

Thickness: 0.6/0.75/1.0/1.2/1.5 mm

Length: 25 m

Width: Specified, from 100 to 1700 mm

Package: Delivered stacked on pallets 1200x800 mm

Weight: 0.6 mm: 0.77 kg/m²

0.75 mm: 0.97 kg/m² 1.0 mm: 1.29 kg/m² 1.2 mm: 1.55 kg/m² 1.5 mm: 1.94 kg/m²

Sd-value: 0.6 mm: 19.2 m

0.75 mm: 24 m 1.0 mm: 32 m 1.2 mm: 38,4 m 1.5 mm: 48 m

Physical properties

For detailed product data, please see corresponding Declaration of Performance.

Storage

Store cool and dry in the original packaging. There are no limitations in shelf life.

Approvals, Certificates & Specifications

CE EN 14909, CE EN 13984, ATG approval.





